

Regal Whiteⁿ SR: .68 IE: .86 SRI: 82

Sierra Tan SR: .35 IE: .86 SRI: 37



Patina Green SR: .29 IE: .87 SRI: 29



Slate Blue SR: .26 IE: .85 SRI: 24



Brandywine SR: .26 IE: .85 SRI: 24



Bone Whiteⁿ SR: .72 IE: .84 SRI: 87



Medium Bronze SR: .30 IE: .87 SRI: 31



Hemlock Green SR: .28 IE: .87 SRI: 28



Regal Blue SR: .28 IE: .86 SRI: 27



Dove Grey SR: .49 IE: .87 SRI: 56



Almond[∆] SR: .63 IE: .86 SRI: 75



Mansard Brown SR: .29 IE: .86 SRI: 29



Classic Green SR: .26 IE: .84 SRI: 24




Terra Cotta SR: .34 IE: .87 SRI: 36



Slate Gray[∆] SR: .37 IE: .86 SRI: 39



Sandstone[∆] SR: .54 IE: .86 SRI: 63



Dark Bronze SR: .26 IE: .84 SRI: 24



Hartford Green* SR: .10 IE: .82 SRI: 2



Banner Red SR: .42 IE: .84 SRI: 45



Charcoal SR: .32 IE: .85 SRI: 32



Surrey Beige[∆] SR: .40 IE: .86 SRI: 43



Extra Dark Bronze* SR: .05 IE: .89 SRI: N/A



Teal SR: .28 IE: .87 SRI: 28



Colonial Red SR: .34 IE: .86 SRI: 35



Matte Black SR: .27 IE: .86 SRI: 26

Mica Colors"





Bright Silver[△] S66 SR: .60 IE: .77 SRI: 68



Silversmith[∆] S15 SR: .53 IE: .78 SRI: 59



Champagne S20 SR: .37 IE: .83 SRI: 38



Pewter S11 SR: .36 IE: .85 SRI: 38



Bright Copper^Δ S25 SR: .49 IE: .85 SRI: 55



Sierra Tan SR: .46 IE: .87 SRI: 52



Classic Green SR: .31 IE: .87 SRI: 32



Slate Gray SR: .37 IE: .86 SRI: 39



Hartford Green SR: .08 IE: .89 SRI: 3



Medium Bronze SR: .30 IE: .86 SRI: 30



Slate Blue SR: .30 IE: .87 SRI: 31



Dark Bronze SR: .28 IE: .86 SRI: 27



Matte Black SR: .26 IE: .86 SRI: 25



Colonial Red SR: .31 IE: .86 SRI: 31

Acrylic Coated Galvalume also available (not pictured)

SR = Solar Reflectivity IE = Initial Emissivity SRI = Solar Reflective Index



Colors shown are as close to actual colors as allowed by the printing process. Actual metal samples are available. Colors may appear different when viewed at different angles and under different lighting conditions. Due to product improvements, changes and other factors, we reserve the right to change or delete information herein without prior notice.



*All Standard Stocked colors are ENERGY STAR® approved except Hartford Green, Extra Dark

 $[\]mbox{\ensuremath{\square}}$ LEED $\mbox{\ensuremath{\square}}$ compliant for low slope and steep slope

[△] LEED° compliant for steep slope only

ARCHITECTURAL PVDF				STEEL			ALUMINUM				
FABRAL COLOR	SR	IE	SRI	26GA.‡	24GA.†	22GA.‡	18GA.‡	.032"†	.040"†	.050" [†]	.063"†
Regal White	.68	.86	82		• = 4 +	•	•	• =			•
Bone White	.72	.84	87		•	•	•	•	•	•	
Almond	.63	.86	75		•			•	•	•	
Sandstone	.54	.86	63		• = 4+	•		•	•	•	
Surrey Beige	.40	.86	43		•+	•		•	•	•	
Sierra Tan	.35	.86	37	LG	•			•	•	•	
Medium Bronze	.30	.87	31	LG	• = +	•	•	•	•	•	•
Mansard Brown	.29	.86	29		•			•	•	•	
Dark Bronze	.26	.84	24	LG	• = 4 +	•	•	• =	•	•	•
Extra Dark Bronze	.05	.89	n/a		•			•		•	
Patina Green	.29	.87	29		•			•			
Hemlock Green	.28	.87	28		•						
Classic Green	.26	.84	24	LG	• =	•		•	•		
Hartford Green	.10	.82	2	LG	•			•		•	
Teal	.28	.87	28		•						
Regal Blue	.28	.86	27		•			•			
Slate Blue	.26	.85	24	LG	•			•			
Terra Cotta	.34	.87	36		•						
Banner Red	.42	.84	45		•			•			
Colonial Red	.34	.86	35	LG	•			•			
Brandywine	.26	.85	24		•			•			
Dove Grey	.49	.87	56		•			• ■		•	
Slate Gray	.37	.86	39	LG	• •			•	•		
Charcoal	.32	.85	32		•	•		•	•	•	
Matte Black	.27	.86	26	LG	•	•		•	•	•	
Bright Silver	.60	.77	68		•			• =	•	•	
Silversmith	.53	.78	59		•			•			
Champagne	.37	.83	38		•			•			
Pewter	.36	.85	38		•			•			
Bright Copper	.49	.85	55	•	• =			• •			

PAINT PERFORMANCE PROPERTIES	HOT DIPPED GALVANIZED STEEL OR GALVALUME®	ALUMINUM			
Accelerated Weathering ASTM D 4587 (Drew Cycle Weatherometer) ASTM G 23	Hours: 3,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max Hours: 5,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max	Hours: 3,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max Hours: 5,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max			
Salt Spray ASTM B 117	Hours: 1,000 Total Scribe: Rating 7 ¹ / ₁₆ " (1.6mm) Field: Rating 10, no blisters	Hours: 3,000 Total Scribe: Rating 10, no creepage Field: Rating 10, no blisters			
Humidity ASTM D 2247	Hours: 2,000 Total Rating: 10, no blisters	Hours: 3,000 Total Rating: 10, no blisters			
Formability ASTM D 4145	0Т-3Т	0Т-3Т			
ASTM D 522 (Elongation over ¹ / ₈ " mandrel)	No cracking No loss of adhesion	No cracking No loss of adhesion			
Pencil Hardness ASTM D 3363	НВ-2Н	НВ-2Н			
Abrasion Resistance ASTM D 968	55-75 Liters of falling sand	55-75 Liters of falling sand			
Specular Gloss ASTM D 523	20-35 at 60°	20-35 at 60°			
Reverse Impact ASTM D 2794	2 x Metal thickness in inch-lbs. No loss of adhesion	11/ ₂ x Metal thickness in inch-lbs. No loss of adhesion			
Flame Test ASTM E 84	Class A rated coating	Class A rated coating			

- † Standard Coil Width is 48.25"
- ‡ Standard Coil Width is 44.375"
- Available in Standard Coil Width.
- Available in 40.25" Coil Width.
- ▲ Available in 38" Coil Width.
- ◆ Available in 44.375" Coil Width.
- LG Refer to website for reflective ratings

NOTES ON AVAILABILITY:

- 1. 26ga, 24ga, .032", .040", .050" & .063" are standard 48.25" in width, 22ga & 18ga are 44.375" in width for painted items.
- 2. Standard inventory is non-embossed. Please contact us for the availability of stucco embossing.
- 3. Protective strippable film is available upon request.
- 4. Mica colors are subject to premium pricing. Due to the unique effect of the Mica finishes, appearances many vary from batch to batch.
- 5. Subject to change without notice.
- 6. Unpainted, acrylic coated, Aluminum-Zinc Alloy steel (AZ-55) is maintained in: 26ga x 20", 26ga x 28", 26ga x 48.25", 24ga x 20", 24ga x 24", 24ga x 28", 24ga x 48.25", 22ga x 44.375", 22ga x 48.25", 20ga x 44.375" and 18ga x 44.375".
- 7. All colors are supplied in Medium Gloss (20-35 at 60°). Low Gloss available subject to minimum coating run.

Fabral® standard architectural colors and finishes feature 70% polyvinylidene fluoride (PVDF) resin paint systems to ensure long term color retention and performance. Custom colors and finishes are also available. Minimum quantities and set up charges may apply.